

NOTES TECHNIQUES

DONNEES TECHNIQUES

www.thdcongo.com - info@thdcongo.com - Tel. 099.99.15.447

LONGUEUR MAXIMALE EN FONCTION DE LA CHUTE DE TENSION



Equipements



220 V MONOPHASE

cosφ = 1

Chute de tension 3%

s (mm²)

kW	A	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240	
0,5	2,3	100	165	265	395												
1	4,6	50	84	135	200	335	530										
1,5	6,8	33	57	90	130	225	355	565									
2	9,0	25	43	68	100	170	265	430	595								
2,5	11,5	20	34	54	80	135	210	340	470	630							
3	13,5	17	29	45	66	110	180	285	395	520							
3,5	16	14	24	39	56	96	155	245	335	450							
4	18		21	34	49	84	135	210	295	395	580						
4,5	20		19	30	44	75	120	190	260	350	515						
5	23			27	39	68	105	170	235	315	460	630					
6	27			23	32	56	90	140	195	260	385	530					
7	32				28	48	76	120	170	225	330	460	570				
8	36					42	67	105	145	195	290	400	500	620			
9	41					38	60	94	130	175	255	355	440	550			
10	45					34	54	84	120	155	230	320	400	495	615		
12	55						45	70	98	130	190	265	330	410	510		
14	64						38	60	84	110	165	230	285	350	435	560	
16	73							53	74	99	145	200	250	305	380	500	
18	82							47	65	88	125	175	220	270	340	440	
20	91		Limite d'échauffement							59	79	115	160	200	245	310	400
25	114									64	98	130	150	195	245	315	
30	136										77	105	135	165	205	265	
35	159											90	115	140	175	225	
40	182											80	100	125	155	200	
45	205												89	110	135	175	
50	227													98	120	160	
60	273														100	140	
70	318															115	

Ces informations sont données à titre indicatif. Une vérification s'impose lors de la mise en pratique.

s (mm²)

kW	A	1,5	2,5	4	6	10	16	25	35	50	70	95	120	150	185	240	
2,5	5	190	325	510	745												
3	6	160	270	420	620												
3,5	7	135	230	365	540	895											
4	8	120	200	320	470	785											
4,5	9	105	180	285	420	700											
5	10	96	165	255	375	630	970										
6	12	79	135	210	315	525	810										
7	14	68	115	180	270	455	700										
8	16	60	105	160	240	400	610	940									
9	18	51	92	145	215	355	550	850									
10	19		84	130	190	320	500	780									
12	23		69	110	160	265	415	640	880								
14	27			94	140	230	355	550	750								
16	31			81	120	200	315	485	655	860							
18	35				110	180	280	430	580	770							
20	38				98	160	255	390	520	690							
25	48					130	205	315	420	555	760						
30	57						170	260	355	465	640	840					
35	67						145	225	300	400	550	730					
40	76							195	260	350	480	640	745				
45	86							175	235	310	430	565	670	770			
50	95							160	215	285	385	510	600	695			
60	114								180	235	320	420	500	580	680		
70	133			Limite d'échauffement							200	275	365	430	495	580	
80	152										240	315	375	430	510	600	
90	171										215	280	335	385	445	535	
100	190											250	300	350	405	480	
120	228												250	290	340	400	
140	266													250	290	345	
160	304														255	300	
180	342															265	

Ces informations sont données à titre indicatif. Une vérification s'impose lors de la mise en pratique.